

Load bank 100 kW – Low Delta T

About the product

The new 100 kW Low Delta T load bank has been specially designed for Data Center testing. The compact design allows it to go through standard doors.

It is also possible to connect up to 48 load banks together and to pilot the whole fleet with only computer running a dedicated supervision software.



Technical Description

Info	Values
Nominal power	105 kW (in Triphase) 33 kW (in Monophase)
Max voltage	400V Triphase – 50/60Hz 230V Monophase
Resolution	5 kW
Power supplies	Powerlocks
Auxiliary power supply	Selective switch int/ext Auxiliary plug 400V 16 A (3 phases+ground)
Air flow	Forced horizontal
Securité	Emergency stop button
Control	Supervisory PLC Possibility to configure test cycles – Data extraction

Info	Values
Height	1222 mm
Depth	1230 mm
Width	770 mm
Weight	180 kg
External protection	Epoxy powder painting
Handling	Wheels Lifting O-ring
Manufacturing	Made in FRANCE

Load bank 100 kW – Low Delta T

Accessories

Cables H07RNF with Powerlocks on one end and cossed M12 on other end(4 cables included)

- 3 phases + Neutral (Powerlock)
- 1 ground
- 1 cable for monitoring



- Rentaload remote control on PC

Connection

